

GBS

SERIES
Briggs Stratton
VANGUARD or INTEK
Gasoline Driven Portable Generator Set

GENPOWER[®]
GENERATOR

GBS 130 ME

STANDARD SPECIFICATIONS

Engine

- Type :Vanguard or Intek
- Revocation: 3000 RPM
- Cooling: Air Cooled
- Electronic Ignition
- Starting System : Recoil

Alternator

- Synchron + brushless
- Number of phase: Monophase
- Excitation: Self excitation
- Power Factor (Cos 0): 1
- Insulation class: H /F
- Protection class: IP 21
- Voltage output :Monophase: 230 V
- Frequene: 50 Hz
- Voltage regulation: + % 5 Chassis
- Direct engine-alternator coupling
- Mounted In stainless steel pipe frame
- Vibration absorber wedges between genset chassis
- Engine top fuel tank the with dial type fuel Indicator (only on some models)
- Mobilise portable wheels under the chassis

Control Panel (Standard]

- Voltmeter AC 1 each
- Thermal circuit breaker 1 each
- Outlet socket, with cover and earth contact 2 each



| | | |
|-------------------------|-----------------|-------------------------|
| Max. Output Power | 230 V | 13 |
| | 400 V | - |
| Frequency | Hz | 50 |
| Power Factor | CosQ | 1 |
| Make | | Briggs Stratton |
| Model | | Vanguard |
| Speed | rpm | 3000 |
| Output Power (3600 rpm) | kW (HP) | 15 (20) |
| Cylinder Displacement | cm ³ | 627 |
| Number Of Cylinder | | 2-V type |
| Cooling System Type | | Air |
| Initial Start System | | Recoil/Electric Starter |
| Fuel Consumption | | 6.7 |
| Fuel Type | lt/hr | Gasoline |
| Oil Capacity | lt | 1.7 |
| Fuel Tank Capacity | lt | 16 |
| | | Senkron |
| Alternator Type | | H/F |
| Insulation Class | | IP 23 |
| Protection Class | | |
| Width | mm | 760(760) |
| Lenght | mm | 860(1100) |
| Height | mm | 760(1200) |
| Weight | kg | 140(230) |

TECHNICAL SPECIFICATIONS