

GNT SERIES

INTER Powered Diesel Generator

GENPOWER®

GENERATOR

GNT 70

Engine Speed rpm	Frequency Hz	Type of Operations	Genset Power		Engine Power (Net)	
			kVA	kW	kWm	bbh
1500	50	Prime Power	64	51	56	76
		Standby Power	70	56	62	84

STANDARD SPECIFICATIONS

Engine

- INTER Heavy duty diesel engine
- Revolution: 1500 rpm
- Water cooled
- Tropical type radiator

Alternator

- VDE 0530 & IEC 34-1 standardizations
- Synchron type brushless
- Automatic voltage regulation (AVR)
- Overload acceptance: 110% for 1 hour, 150% for 2 minutes
- Short circuit resistance: 300 for 10 seconds
- Insulation class: H
- Insulation resistance: 1800 VAC
- Voltage: 230/400 V three phase
- Voltage regulation: $\pm 0,5\%$
- Protection class: IP23
- Power factor (cosq): 0,8
- Frequency: 50 Hz

Manuel Control Panel

- Microprocessed Electronic Control Panel
- Relays
- Protection fuses
- Thermic magnetic circuit breaker (TMS) 3-pole
- Emergency stop button

Automatic Control Panel

- Microprocessed AMF Electronic Control Panel
- Protection fuses
- Battery charger
- Power Transfer (For ATS)
- Emergency stop button

Chassis

- Mounted on the steel base chassis
- Elastic vibration dampers between engine and chassis
- Chassis integrated fuel tank
- Dial type mechanical fuel indicator

Canopy

- Easy lifting and moving
- Metal parts are coated with electrostatic polyester coated, powder painted
- Thermally insulated exhaust system
- Acoustic insulation with rot*proof, moisture-repellent and non-flammable material (per DIN 4102 A2)



ENGINE

Make	INTER
Model	IDE 451 NG
Number of Cylinder	4
Cylinder arrangement	In-line
Cycle	4 stroke
Aspiration	Naturally
Combustion system	Direct injection
Compression ratio	17,5:1
Bore and Stroke	mm 108 x 135
Displacement	lt 5,1
Cooling System	Water Cooled
Total coolant capacity	lt 15
Total lubrication	lt 10
Governor Type	Mechanic
Electric System	12 VDC
Fuel Consumption %50 Loaded	lt/h 7,7
Fuel Consumption %75 Loaded	lt/h 11,5
Fuel Consumption % 100 Loaded	lt/h 15
Fuel Tank Cap. Open (canopy)	lt 190 (284)

DIMENSIONS

Width w/o Canopy (w/canopy)	mm 800 (1000)
Lenght w/o Canopy (w/canopy)	mm 2020 (2600)
Height w/o Canopy (w/canopy)	mm 1560 (1540)
Weight w/o Canopy (w/canopy)	kg 1040 (1378)

TECHNICAL SPECIFICATIONS

* AAC (Air-to-Air-Cooling): Charged hot air by turbo is cooled by the air radiator in the system.

** WAC (Water-to-Air-Cooling): Charged hot air by turbo is cooled by water in the cooling system.

GENPOWER, reserves the right to modify the characteristics of it's product at any time in order to incorporatie the latest technological developments.