

# GVP SERIES

**VOLVO PENTA Powered**  
Diesel Generator

# GENPOWER®

GENERATOR

## GVP 500

Engine Speed rpm	Frequency Hz	Type of Operations	Genset Power		Engine Power (Net)	
			kVA	kW	kWm	bbh
1800	60	Prime Power	455	364	392	533
		Standby Power	500	400	431	586

STANDARD SPECIFICATIONS

### Engine

- VOLVO PENTA Heavy duty diesel engine
- Revolution: 1800 rpm
- Water cooled
- Tropical type radiator

### Alternator

- VDE 0530 & IEC 34-1 standardizations
- Synchron type brushless
- Automatic voltage regulation (AVR)
- Overload acceptance: 110% for 1 hour, 150% for 2 minutes
- Short circuit resistance: 300 for 10 seconds
- Insulation class: H
- Insulation resistance: 1800 VAC
- Voltage: 277/480 V three phase
- Voltage regulation:  $\pm 0,5\%$
- Protection class: IP23
- Power factor (cos $\phi$ ): 0,8
- Frequency: 60 Hz

### Manuel Control Panel

- Microprocessed Electronic Control Panel
- Relays
- Protection fuses
- Thermic magnetic circuit breaker (TMS) 3-pole
- Emergency stop button

### Automatic Control Panel

- Microprocessed AMF Electronic Control Panel
- Protection fuses
- Battery charger
- Power Transfer (For ATS)
- Emergency stop button

### Chassis

- Mounted on the steel base chassis
- Elastic vibration dampers between engine and chassis
- Chassis integrated fuel tank
- Dial type mechanical fuel indicator

### Canopy

- Easy lifting and moving
- Metal parts are coated with electrostatic polyester coated, powder painted
- Thermally insulated exhaust system
- Acoustic insulation with rot\*proof, moisture-repellent and non-flammable material (per DIN 4102 A2)



### ENGINE

Make	Volvo Penta
Model	TAD 1344 GE
Number of Cylinder	6
Cylinder arrangement	In-line
Cycle	4 stroke
Aspiration	Turbocharged AAC*
Combustion system	Direct injection
Compression ratio	18,1:1
Bore and Stroke	mm 131 x 158
Displacement	lt 12,78
Cooling System	Water Cooled
Total coolant capacity	lt 44
Total lubrication	lt 36
Governor Type	Electronic
Electric System	24 VDC

Fuel Consumption %50 Loaded	lt/h 47,6
Fuel Consumption %75 Loaded	lt/h 69,6
Fuel Consumption % 100 Loaded	lt/h 93,2
Fuel Tank Cap. Open (canopy)	lt 673 (399)

### DIMENSIONS

Width w/o Canopy (w/canopy)	mm 1260 (1600)
Lenght w/o Canopy (w/canopy)	mm 3120 (4600)
Height w/o Canopy (w/canopy)	mm 2040 (2600)
Weight w/o Canopy (w/canopy)	kg 3270 (4220)

TECHNICAL SPECIFICATIONS

\* AAC (Air-to-Air-Cooling): Charged hot air by turbo is cooled by the air radiator in the system.

\*\* WAC (Water-to-Air-Cooling): Charged hot air by turbo is cooled by water in the cooling system.

GENPOWER, reserves the right to modify the characteristics of it's product at any time in order to incorporatie the latest technological developments.